



Holland Air Pumps bv®

# ALMATEC AD50 – 2” Metal Pump



**MAX FLOW RATE:** 400 LPM (105.7 GPM)  
**MAX PRESSURE:** 7 BAR (100 PSI)  
**MAX DIAMETER SOLIDS:** 14 mm (0.55")  
**MAX SUCTION LIFT CAPABILITY:**  
3 m (9.8') Dry, 9 m (29.5') Wet

## WETTED HOUSINGS

### Material

Stainless Steel 316

Stainless Steel polished

### Ship Wt

29 kg (63.9 lbs)

29 kg (63.9 lbs)



## NON-WETTED HOUSINGS

### Description

Center Section

Air Valve

### Material

PE CONDUCTIVE

PETP

## ELASTOMER OPTIONS

### Material

EPDM™

PTFE



NBR

### Temperature limits

-51.1 (-60) to +137.8 (+280) °C (F°)

+4.4 (+40) to +104.4 (+220) °C (F°)

-12.2 (+10) to +82.2 (+180) °C (F°)



**WILDEN** ALMATEC®

## HOLLAND AIR PUMPS BV

De Scheper 260, NL-5688 HP Oirschot, The Netherlands

T +31 499 551000, F +31 499 551005

E-mail: info@hollandairpumps.nl