



Holland Air Pumps bv®

# ALMATEC CX20 - 1/2" Plastic Pump



## WETTED HOUSINGS

**Material**  
PE conductive

**Ship Wt**  
2 kg (4.4 lbs)

## NON-WETTED HOUSINGS

**Description**  
Center Section  
Air Valve


**Material**  
PE conductive  
PETP

## ELASTOMER OPTIONS

**Material**  
EPDM™  
PTFE  
NBR

**Temperature limits**  
-51.1 (-60) to +137.8 (+280) °C (F°)  
+4.4 (+40) to +104.4 (+220) °C (F°)  
-12.2 (+10) to +82.2 (+180) °C (F°)

**MAX FLOW RATE:** 20 LPM (5.3 GPM)  
**MAX PRESSURE:** 7 BAR (100 PSI)  
**MAX DIAMETER SOLIDS:** 2 mm (0.08")  
**MAX SUCTION LIFT CAPABILITY:**  
2 m (6.6') Dry, 8 m (26.2 ') Wet



**WILDEN ALMATEC®**

### HOLLAND AIR PUMPS BV

De Scheper 260, NL-5688 HP Oirschot, The Netherlands  
T +31 499 551000, F +31 499 551005  
E-mail: info@hollandairpumps.nl